

Listing of Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) ~~Method~~ A method of providing a video signal for display of a stream (200) of video data at a rate other than real-time, the video data being built up from frames (212), the method comprising the ~~step of~~ steps of:

real-time rendering of non-contiguous segments (202) of the stream of video data comprising multiple subsequent frames to a first rendered stream;
~~characterised in that the method further comprises the step of:~~

(a) non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames ~~at a speed other than real-time~~ to a second rendered stream; and

(b) multiplexing the first rendered stream and the second rendered stream for simultaneous display on a display device (150),

wherein: i) the first rendered stream is displayed on a first part (310) of the display device [1:] and ii) the second rendered stream is displayed on a second part (320) of the display device; and

wherein the first rendered stream is provided at a first rate and the second rendered stream is provided at a second rate, where the second rate is greater than the first rate.

2. (Currently Amended) ~~Method~~ The method according to claim 1, wherein the second part of the display device is significantly smaller than the full size of the display device and the first part of the display is the complement to the second part.
3. (Currently Amended) ~~Method~~ The method according to claim 1, wherein the first part of the display device is significantly smaller than the full size of the display device and the second part of the display is the complement to the second part.
4. (Currently Amended) ~~Method~~ The method according to claim 1, wherein the first part of the display device and the second part of the display device have mutually equal sizes.
5. (Currently Amended) ~~Method~~ The method according to claim 1, wherein the method further comprises the steps of:
- (a) providing a first bar (412) representative of the stream of video data; and
 - (b) indicating on the first bar the location of the first rendered stream that is displayed on the first part of the display device.
6. (Currently Amended) ~~Method~~ The method according to claim 1, wherein the method further comprises the steps of:
- (a) providing a second bar (422) representative of the stream of video data; and
 - (b) indicating on the second bar a location of the second rendered stream that is displayed on the second part of the display device.

7. (Cancelled)

8. (Currently Amended) ~~Method~~ The method according to claim 5, wherein the method further comprises the step of:

indicating on the first bar a location of the second rendered stream that is displayed on the second part of the display device.

9. (Currently Amended) ~~Method~~ The method according to claim 1, wherein the method further comprises the step of:

providing an indicator indicative of the direction of the non real-time rendering.

10. (Currently Amended) ~~Method~~ The method according to claim 1, further comprising the step of:

providing an audio signal at real-time, synchronised with the first rendered stream.

11. (Currently Amended) ~~Apparatus (110)~~ An apparatus for providing a video signal for display of a stream (200) of video data at a rate other than real-time, the video data being built up from frames (212), the ~~method~~ apparatus comprising:

a first rendering unit (116) for real-time rendering of non-contiguous segments (202) of the stream of video data comprising multiple subsequent frames to a first rendered stream;

~~characterised in that the apparatus further comprises:~~

~~(a)~~ a second rendering unit ~~(118)~~ for non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames ~~at a speed other than real-time~~ to a second rendered stream; and

~~(b)~~ a multiplexer ~~(120)~~ for multiplexing the first rendered stream and the second rendered stream for simultaneous display on a display device ~~(150)~~,

wherein: ~~i)~~ the first rendered stream is displayed on a first part ~~(310)~~ of the display device ~~[[;]]~~ and ~~ii)~~ the second rendered stream is displayed on a second part ~~(320)~~ of the display device; and

wherein the first rendered stream is provided at a first rate and the second rendered stream is provided at a second rate, where the second rate is greater than the first rate

12. ~~(Currently Amended) Record carrier (124), comprising: a storage medium having instructions, that when executed by a computing platform, result in execution of the method of providing a video signal for display of a stream (200) of video data at a rate other than real-time, the video data being built up from frames (212), the method comprising the step of real-time rendering of non-contiguous segments (202) of the stream of video data comprising multiple subsequent frames to a first rendered stream; characterised in that the method further comprises the step of:~~

A computer-readable medium storing programmable instructions configured for being executed by at least one processor for performing a method suitable for providing a video signal for display of a stream of video data at a rate other than real-time, the video data being built up from frames, the method comprising:

real-time rendering of non-contiguous segments of the stream of video data comprising multiple subsequent frames to a first rendered stream;

(a) non real-time rendering of the stream of video data by rendering pre-determined non subsequent frames ~~at a speed other than real-time~~ to a second rendered stream; and

(b) multiplexing the first rendered stream and the second rendered stream for simultaneous display on a display device ~~(150)~~,

wherein ~~i)~~ the first rendered stream is displayed on a first part ~~(310)~~ of the display device ~~[[;]]~~ and ~~ii)~~ the second rendered stream is displayed on a second part ~~(320)~~ of the display device; and

wherein the first rendered stream is provided at a first rate and the second rendered stream is provided at a second rate, where the second rate is greater than the first rate.

13. (Cancelled)